

Be-Tech
Premium Fingerprint Digital Door Lock

- Digital Cylindrical Latch Lock
- Fingerprint
- 60/70mm Adjustable Backset Cylindrical Latch
- Matte Black



Unlock your life with smart solution
Leave your home security to Be-Tech



One-Touch Fingerprint Verification

One-touch Fingerprint verification technology has been applied to conveniently read a fingerprint in one shot.



Operation Status Notification

Whenever any operation is made, the LED indicator informs you what is happening through different colors and signs.



Tubular Latch Locking Mechanism

International standard jimmy proofing tubular latch.



Automatic Locking

Door lock will be locked automatically after opening door a few seconds. (Manual operation is also available)



Easy To Install

Easily to replace the existing mechanical lock to a fingerprint lock.



Anti-Panic Exit System

For convenience and in case of emergency, it allows you to open the door by simply turning its handle from inside.




Low Battery Warning Signal

LED light reminder of low battery during door access will alert you to replace batteries.



Convenient



Model



Reliable



Safe



Specification

Parts	Specifications	Remarks
Front(Front Body)	168.5(W)×60(H)×71(D)mm (with handle)	Temperature: Workable -30°C~66°C Humidity: Workable 20%~93% ± 2RH
Back(Back Body)	168.5(W)×60(H)×71(D)mm (with handle)	
Door Thickness	Applicable Range 35-60mm	
Material	Aluminum Alloy + ABS	
Lock case	Tubular latch (Galvanized steel)	
Fingerprint	Up to 20 Groups (3 Master Fingerprints & 17 User Fingerprints)	
Battery	3X1.5V AAA alkaline batteries(Operating voltage: 3.3~4.5V)	Last up to 8 months(20 times used a day)
Applicable Area	For indoor use only .Maximum torque of handle no more than 25 N.m. Door weight no more than 100 Kg.	

Contact us:

Smart Life, Your Life



Guangdong Be-Tech Security Systems Limited
 No.17, Ronggui Technology Industrial Park
 Keyuan 3rd Road, Shunde, Foshan
 Guangdong, P.R. China
 Tel: +86 757 28376123 | Fax: +86 757 28308823
 E-mail: export@be-tech.com.cn | www.betechlock.com

Specifications may change without notice.

ID:04-BTFMA42C2005-E1-02