



Smart Door Lock Lock Case



DIN-55

Type: DIN Profile Electronic Mortise
Backset: 55mm
Center distance: 72mm
Faceplate: 20/24mm
Latches: SUS304
Standard: Qualified EN14846, EN1634- 1 hour
Life cycle: 200.000 cycles



DIN-65

Type: DIN Profile Electronic Mortise
Backset: 65mm
Faceplate:20/24mm
Center distance:72mm
Latches: SUS304
Standard: Qualified EN14846, EN1634- 1 hour
Life cycle: 200.000 cycles



DIN-80

Type: DIN Profile Electronic Mortise
Backset: 80mm
Faceplate:20 / 24mm
Center distance:72mm
Latches: SUS304
Standard: Qualified EN14846, EN1634- 1 hour
Life cycle: 200.000 cycles



EURO-65

Type: Electronic Mortise
Backset: 65mm
Faceplate:24mm
Center distance: 93.5mm
Latches: SUS304
Standard:Qualified EN14846, EN1634- 1 hour, UL 10c
Life cycle: 200.000 cycles

Easy Access
Leading Keyless Solutions Since 1992



Special for smart door lock,
CE-compliant, with a service
life up to 200,000 cycles.

Guangdong Be-Tech Security Systems Limited

No.17,Ronggui Technology Industrial Park Keyuan 3rd Road, Shunde, Foshan, Guangdong,P.R.China Tel:+86 757 28376123 Fax:+86 757 28308823
E-mail:export@be-tech.com.cn | www.betechlock.com | www.betechiot.com

Specifications may change without notice.

ID:04-BTFMTA42C2604-E1-01



7068

Type: Mechanical Mortise
Backset: 70mm
Faceplate: 24mm
Center distance: 68mm
Latches: SUS304
Standard: Qualified EN14846
Life cycle: 100.000 cycles



ANSI-51A

Type: Electronic Mortise
Backset: 70mm
Faceplate: 28/31.5mm
Center distance: 93.5mm
Latches: SUS304
Standard: Qualified EN14846 , UL 10c
Life cycle: 200.000 cycles



AN2

Type: Electronic Mortise
Backset: 60mm
Faceplate: 24mm
Center distance: 68mm
Latches: SUS304
Standard: Qualified EN14846
Life cycle: 100.000 cycles



7068

Type: Electronic Mortise
Backset: 70mm
Faceplate: 24mm
Center distance: 68mm
Latches: SUS304
Standard: Qualified EN14846
Life cycle: 100.000 cycles



6085

Type: Mechanical Mortise
Backset: 60mm
Faceplate: 24mm
Center distance: 85mm
Latches: SUS304
Life cycle: 100.000 cycles



AN16-03

Type: Mechanical Mortise
Backset: 60mm
Faceplate: 24mm
Center distance: 68mm
Latches: SUS304
Standard: Qualified EN14846
Life cycle: 100.000 cycles